

SPEC CARD#: 39926
ITEM.....: 51-000-13
DESCRIP....: CAMSHAFT, P8 PONTIAC ROLLER
GRIND#.....: Camshaft, 2522B/12275B R 112.0 + .0

CUSTOMER INSTRUCTIONS:

HYDRAULIC.....: N

	<u>INTAKE</u>	<u>EXHAUST</u>
LOBE ID.....:	2522B	12275B
VALVE ADJUSTMENT.....:	.016	.016
VALVE LIFT.....:	.821	.814
CHECKING HEIGHT.....: .020		
ADVERTISED DURATION...:	300	311
VALVES TIMING @.....: .050		
VALVES OPEN.....:	24	73
VALVES CLOSED.....:	68	29
DURATION @ 0.050.....:	272	282
LOBE LIFT.....:	.4830	.4790
ROCKER RATIO.....:	1.70	1.70
BANK ANGLE.....:	STD	STD
CENTER LINE.....:	112.0	112.0

LOBE SEPARATION.....: 112.0	CAM ADVANCE.....: .0
CORE TYPE.....: R	GEAR TYPE.....: S
SMALL BASE CIRCLE.....: N	REAR PUMP DRIVE.....: N
REVERSE ROTATION.....: N	FUEL PUMP DRIVE.....: Y
JOURNAL DIAMETER.....:	LOBE SPACING.....: STD
MATERIAL.....: 8620	FIRING ORDER.....: STD

CORE SELECTED.....: C51-13B

COMMENTS.....: