

6423211

FILTER SERVICE INSTRUCTIONS

**REMOVE FILTER FROM SCREEN-WASH IN KEROSENE-SQUEEZE
-DO NOT WRING-DRY COMPLETELY WITH LOW PRESSURE AIR.
DIP IN 10W30 OIL-CAREFULLY SQUEEZE OUT EXCESS OIL.**

**REPLACE FILTER SO THAT TOP AND BOTTOM OF
SCREEN IS COMPLETELY COVERED ALL AROUND
SEE OWNERS GUIDE FOR FREQUENCY OF SERVICE**



**REPLACE WITH
A274C
AIR FILTER**

6423211

FILTER SERVICE INSTRUCTIONS

**REMOVE FILTER FROM SCREEN-WASH IN KEROSENE-SQUEEZE
-DO NOT WRING-DRY COMPLETELY WITH LOW PRESSURE AIR.
DIP IN 10W30 OIL-CAREFULLY SQUEEZE OUT EXCESS OIL.**

**REPLACE FILTER SO THAT TOP AND BOTTOM OF
SCREEN IS COMPLETELY COVERED ALL AROUND
SEE OWNERS GUIDE FOR FREQUENCY OF SERVICE**



**REPLACE WITH
A274C
AIR FILTER**